

REGLOPLAS

350LD

The temperature control unit for thermal oil up to 350 °C

- Control system RT200 or RT100
- High heating capacity max. 80 kW (2 x 40 kW)
- Pump with high flow rate: 90 l/min per circle
- Leak-free pump with magnetic coupling
- Solid-state relay instead of heating contactor



Heat transfer medium	Outlet temperature	Heating capacity at 400V	Cooling capacity	Pump capacity/Type
Oil	350 °C	20 kW	280 °C 30 kW 280 °C 85 kW	FM65 90 l/min 2.8 kW

Regloplas 350 LD

Technical data			
Outlet temperature			
max.	°C	350	
Heat transfer medium		Oil	
Filling quantity	l	24.0	
Expansion volume	l	20.0	
Heating capacity at 400V	kW	20	
Cooling capacity	kW	30	85
Cooler		1K	2K
at outlet temperature	°C	280	280
at cooling water temperature	°C	20	20
Pump capacity/Type		FM65	
Flow rate max.	l/min	90	
Power consumption	kW	2.8	
Pressure max.	bar	9.5	
Control system		RT100	
Measuring mode (Standard)		Pt100	
Operating voltage	V/Hz	200-600 V, 50/60 Hz	
Connections			
Outlet/Inlet		G3/4" IG	
Cooling water mains		G3/4"	
Degree of protection		IP54	
Dimensions W/H/D	mm	546/1621/1465	
Weight	kg	373	
Color	RAL	9006/7016	
Ambient temperature			
max.	°C	40	
Noise level	db (A)	< 70	

Standard equipment

- RT100 control system
- Unit in IP54 protection degree
- Leak-free pump
- Filter in the main circuit
- Filter in the cooling water circuit
- Water circuit of non-rusting materials
- Pressure gauge outlet
- Pressure gauge inlet
- Solid-state relay (SSR) instead of heating contactor

Options

- Inert gas blanket
- Bypass cooler 2k
- Electronic flow measurement
- RT200 control system